





Single-rotor rake	Standard working widths	Working widths Hydraulic / Twin swath function	Arms per rotor	Rotor diameter
TOP 342	3.40 m	–	10	2.80 m
TOP 382	3.80 m	–	11	3.00 m
TOP 422	4.20 m	–	12	3.30 m
TOP 462	4.60 m	–	12	3.70 m
TOP 422 A	4.20 m	–	12	3.30 m
TOP 462 A	4.60 m	–	12	3.70 m




### Twin rotor rake with centre swath placement

TOP 612	5.90 m	–	11	2.82 m
TOP 612 C	5.90 m	–	11	2.80 m
TOP 702 C	6.45 m – 6.85 m	6.25 m – 6.90 m	11	3.07 m
TOP 762 C CLASSIC	6.90 m – 7.40 m	6.75 m – 7.50 m	11	3.30 m
TOP 762 C	6.90 m – 7.40 m	6.75 m – 7.50 m	13	3.30 m
TOP 842 C	7.70 m – 8.40 m	7.70 m – 8.40 m	13	3.70 m
TOP 962 C	8.90 m – 9.60 m	8.90 m – 9.60 m	15	4.30 m



### Twin rotor rake with side swath placement

TOP 652	6.40 m	–	10 + 12	3.00 m / 3.15 m
TOP 662	6.55 m	7.30 m	12	3.07 m
TOP 722	6.80 m	7.60 m	13	3.30 m
TOP 812	7.60 m	–	13	3.70 m
TOP 632 A	3.40 m – 6.30 m	6.80 m	12	3.00 m
TOP 692 A	3.70 m – 6.90 m	7.40 m	12	3.30 m



### Four-rotor rakes with centre swath placement

TOP 1252 C	8.00 – 12.50 m	8.00 – 12.50 m	13	3.30 m
TOP 1403 C	8.50 – 14.00 m	8.50 – 14.00 m	13	3.70 m / 3.30 m

Tyres	Transport width (with tine arms)	Transport length	Transport / Parking height	Weight
–	1.95 m (2.80 m)	–	–	474 kg
–	1.95 m (3.00 m)	–	–	495 kg
–	2.29 m	–	–	730 kg
–	2.29 m	–	–	765 kg
–	2.13 m	–	–	820 kg
–	2.48 m	–	–	860 kg

–	2.70 m	3.13 m	3.40 m / 2.70 m	1010 kg
260/70-15.3	2.55 m	5.15 m	3.52 m / 2.92 m	1470 kg
260/70-15.3	2.55 m / 2.90 m	5.83 m	3.80 m / 3.30 m	1680 kg
260/70-15.3	2.55 m / 2.90 m	5.83 m	3.99 m / 3.50 m	1800 kg
260/70-15.3	2.55 m / 2.90 m	5.83 m	3.99 m / 3.50 m	1940 kg
340/55-16	2.90 m	6.50 m	3.99 m / 3.50 m	2580 kg
340/55-16	2.95 m	7.00 m	3.95 m / 3.85 m	3130 kg

260/70-15.3	2.95 m	7.90 m	3.95 m / 3.43 m	2000 kg
260/70-15.3	2.55 m / 2.90 m	8.10 m	3.99 m / 3.99 m	1990 kg
340/55-16	2.61 m / 2.90 m	8.90 m	3.99 m / 3.60 m	2490 kg
340/55-16	2.90 m	9.70 m	3.99 m / 3.60 m	2810 kg
–	1.90 m	7.30 m	–	1700 kg
–	2.13 m	7.80	–	1750 kg

500/50-17	3.00 m	10.25 m	3.99 m / 3.40 m	6315 kg
620/40-22.5	3.00 m	10.60 m	3.99 m / 3.99 m	6450 kg