

Tipping Trailers

TR4 & TR6 Tipping Trailers



Grain/Mesh sides optional for TR4 & TR6



- Ideal general purpose trailers.
- Reinforced sides and hinge points.
- High tip for clean unloading
- Hydraulic brakes & lights as standard
- Lights fitted in protective channel.
- Slim-line reinforced draw-bar with hose and cable stand as standard.
- All 4 sides are removable and are fabricated in one piece (no water traps).
- 4mm Reinforced floor and side chimes fabricated in one piece for extra strength.
- Handbrake as standard
- Galvanised mesh sides optional.
- Grain sides/door optional
- Galvanised option by special order

TR4 Trailer

- 4000 Kg capacity
- Size 3m x 1.9m x 0.56m (9ft10 x 6ft 3" x 22")

TR6 Trailer

- 6000 Kg capacity
- Size 3.7m x 2.15 x 0.56m (12ft x 7ft x 22")



Model	Body Length	Width	Floor Thickness	Sides height (cm)	Loading height to trailer floor (cm)	Loading height to top of sides (cm)
TR4	3m (9ft10")	1.9m (6ft3")	4mm	56cm	97cm	153cm
TR6	3.76m (12ft4")	2.15m (7ft)	4mm	56cm	100cm	156cm

	Lights	Brakes	Unladen Weight	Cubic capacity (m3)	Wheel Size Standard	Wheel Size Optional
TR4	YES	YES	975kg	3.2	10/75/15.3	11.5/80/15.3
TR6	YES	YES	1464kg	4.53	12.5/80/15.3	400/16/15.5

Optional Extra's

Model	Cubic capacity with grain sides (m3)	Side height with grain sides (cm)	Side height with mesh sides (cm)
TR4	5.82	112cm	118cm
TR6	8.34	112cm	112cm

Trailers Wheels

Standard Wheels

TR1	TR2	TR4	TR6, TR8, TR8M & TRF21	TR10, & TR10M	TRF25	TR12 & TR14
						
23/10.5/12	10/80/12	10/75/15.3	12.5/80/15.3	385/55/22.5	385/65/22.5	550/45/22.5

Wheels Options

TR2	TR4	TR6, TR8 & TR8M	TR10 & TR10M	TRF25
				
26/12/12 10/80/12.5 26/12/12.5 (Turf Tyre)	11.5/80/15.3	400/16/15.5	500/50/17	550/45/22.5

	TR1	TR2	TR4	TR6	TR8	TR8M
Wheel Size Standard	23/10.5/12	10/80/12	10/75/15.3	12.5/80/15.3	12.5/80/15.3	12.5/80/15.3
Wheel Size Optional	N/A	26/12/12.5	11.5/80/15.3	400/16/15.5	400/16/15.5	400/16/15.5

	TR10	TR10M	TR12	TR14	TRF21	TRF25
Wheel Size Standard	385/55/22.5	385/55/22.5	550/45/22.5	550/45/22.5	12.5/80/15.3	385/65/22.5
Wheel Size Optional	500/50/17	500/50/17	385/65/22.5	385/65/22.5	400/60/15.5	550/45/22.5