

# Tipping Trailers

14 Ton Monocoque Tipping Trailer (TR14)










- Heavy Duty 14,000kg Agricultural trailer designed to satisfy the requirements of modern trailer operations.
  - All chassis and body parts are manufactured from high tensile steel plate and hollow section to help reduce weight and increase payload without compromising structural strength.
  - Unique design sprung draw bar provides excellent ride characteristics working in combination with the multi leaf spring bogie suspension to reduce stress on the towing vehicle and operator.
  - Tapered body and twin heavy duty tipping rams ensure a fast and clean unloading time with all hydraulic pipes safely concealed within the chassis.
  - 10 stud heavy duty commercial axle, brakes and lights.
  - 40mm EN8 towing eye, skid and skid carrier
  - Hydraulic hose carrier and access ladder
  - 550/45/22.5 flotation tyres.
- **Options include:**
- Hydraulic back door complete with locking safety valve to avoid accidental spillage.
  - Galvanised silage extension kit complete with swinging back door and automatic trip.
  - Front viewing window
  - Grain chute
  - Tarpaulin cover

Model	Sides Height	Floor Thickness	Body Length	Width	Loading Height
TR 14	2.5m	5mm	570cm	242cm	250cm

Lights	Brakes	Unladen Weight	Wheel Size Standard	Wheel Size Optional
Yes	Yes	4320kgs	550/45/22.5 (10 Stud)	385/65/22.5

# Trailers Wheels

## Standard Wheels

TR1	TR2	TR4	TR6, TR8, TR8M & TRF21	TR10, & TR10M	TRF25	TR12 & TR14
						
23/10.5/12	10/80/12	10/75/15.3	12.5/80/15.3	385/55/22.5	385/65/22.5	550/45/22.5

## Wheels Options

TR2	TR4	TR6, TR8 & TR8M	TR10 & TR10M	TR12 & TRF25
				
26/12/12 10/80/12.5 26/12/12.5 (Turf Tyre)	11.5/80/15.3 400/60/15.5	400/16/15.5	500/50/17	550/45/22.5

	TR1	TR2	TR4	TR6	TR8	TR8M
Wheel Size Standard	23/10.5/12	10/80/12	10/75/15.3	12.5/80/15.3	12.5/80/15.3	12.5/80/15.3
Wheel Size Optional	N/A	26/12/12.5	12.5/80/15.3 400/60/15.5	400/16/15.5	400/16/15.5	400/16/15.5

	TR10	TR10M	TR12	TR14	TRF21	TRF25
Wheel Size Standard	385/55/22.5	385/55/22.5	550/45/22.5	550/45/22.5	12.5/80/15.3	385/65/22.5
Wheel Size Optional	500/50/17	500/50/17	385/65/22.5	385/65/22.5	400/60/15.5	550/45/22.5