

Tipping Trailers

10 Ton Tipping Trailer (TR10)



- Ideal general purpose trailer with a large capacity of 10,000kg
- Reinforced half sides for easy fitting with reinforced hinge points
- All 4 side of the trailer are removable
- High tip for clean unloading with high specification H.D 3 stage Tipping Hyd. cylinder
- Hydraulic brakes & lights and reflective triangles as standard.
- Lights fitted in protective channel
- Spring suspension creates less stress on the trailer structure resulting in longer maintenance free operation
- Slim-line reinforced draw-bar with galvanised parking shoe, hose and cable stand as standard
- 4.35m x 2.23m x 60cm (14ft3" x 7ft2" X 2ft)
- Optional Grain sides
- Optional bale extension.

10 Ton Monocoque Tipping Trailer (TR10M)









- Solid construction Monocoque body for extra strength
- Large capacity of 12cu.m
- 4.35m x 2.25m x 1.2m (14ft3" x 7ft2" x 4ft)
- Structural steel 200mm x 100mm box section channel chassis with 8 stud axles on 385/55/22.5 tyres
- Optional tarpaulin cover
- Optional grain shoot

Model	Sides Height	Floor Thickness	Body Length	Width	Loading Height
TR 10	600mm	5mm	4.35m	2.25m	1.8m
TR 10M	1200mm	5mm	4.35m	2.4m	2.39m

Model	Lights	Brakes	Unladen Weight	Wheel Size Standard	Wheel Size Optional
TR 10	YES	YES	2.9 Ton	385/55/22.5	500/50/17
TR 10M	YES	YES	3.2 Ton	385/55/22.5	500/50/17

Trailers Wheels

Standard Wheels

TR1	TR2	TR4	TR6, TR8, TR8M & TRF21	TR10, & TR10M	TRF25	TR12 & TR14
						
23/10.5/12	10/80/12	10/75/15.3	12.5/80/15.3	385/55/22.5	385/65/22.5	550/45/22.5

Wheels Options

TR2	TR4	TR6, TR8 & TR8M	TR10 & TR10M	TR12 & TRF25
				
26/12/12 10/80/12.5 26/12/12.5 (Turf Tyre)	11.5/80/15.3 400/60/15.5	400/16/15.5	500/50/17	550/45/22.5

	TR1	TR2	TR4	TR6	TR8	TR8M
Wheel Size Standard	23/10.5/12	10/80/12	10/75/15.3	12.5/80/15.3	12.5/80/15.3	12.5/80/15.3
Wheel Size Optional	N/A	26/12/12.5	12.5/80/15.3 400/60/15.5	400/16/15.5	400/16/15.5	400/16/15.5

	TR10	TR10M	TR12	TR14	TRF21	TRF25
Wheel Size Standard	385/55/22.5	385/55/22.5	550/45/22.5	550/45/22.5	12.5/80/15.3	385/65/22.5
Wheel Size Optional	500/50/17	500/50/17	385/65/22.5	385/65/22.5	400/60/15.5	550/45/22.5